

OIL TECH

The Lubrication Specialists

TECHNICAL DATA SHEET

PREMIUM UNIVERSAL 15W/50

PRODUCT DESCRIPTION

PREMIUM UNIVERSAL 15W/50 All season, SAE 15W/50 oil for naturally aspirated and turbo-charged gasoline and diesel engines.

APPLICATION

PREMIUM UNIVERSAL 15W/50 All season, high performance SAE 15W/50 engine oil. For normally aspirated and turbo-charged gasoline engines, light commercial diesel engines and four-stroke motorcycle.

PERFORMANCE

Rationalisation of grades and packages: Unrestricted use in normally aspirated and turbo-charged gasoline and diesel engines.

Provides excellent viscometrics: stays in grade and maintains it's characteristics even in very severe operation.

Maintains engine cleanliness.

Suitable for vehicles using LPG fuel, leaded and unleaded fuel.

Compatible with catalytic converters.

Suitable for, vehicles operating in dusty or sandy conditions, stop-start driving.

Excellent protection against wear due to stable lubricating film at full-throttle operation.

Protect against sludging.

Compatible with all gaskets and seals.

Optimum operation of tappets due to the absence of foam.

PERFORMANCE CHARACTERISTICS

- SAE grade 15W/50
- API SL/CF4
- ACEA A2-98 B2-98 E2-96
- CATERPILLAR TO-2
- Military MIL-L2104E
- Military MIL-L-46152B
- Mercedes 229.1

PREMIUM UNIVERSAL 15W/50

TYPICAL INSPECTION

Properties	Unit	Value
SAE Grade		15W/50
Viscosity @ 40 °C	cSt	170
Viscosity @100 °C	cSt	19
Viscosity Index		127
Flash Point°C		210
Density @15°C	g/ml	0.89