

OIL TECH

The Lubrication Specialists

TECHNICAL DATA SHEET

UNIVERSAL HD 30

PRODUCT DESCRIPTION

UNIVERSAL HD 30 A mono grade diesel engine oil for engines requiring a SAE 30 grade oil.

APPLICATION

UNIVERSAL HD 30 A mono grade diesel engine oil designed to meet the requirements of manufacturers calling for an SAE 30 grade oil, with a medium level sulphated ash content. May be used in lawn mower and other small 4 stroke engines such as briggs and stratton.

PERFORMANCE

- Maintains engine cleanliness.
- Prevents rings sticking.
- Reduces piston deposits.
- For use in normally aspirated and turbocharged engines.
- Meets the requirements of Series 2 and Series 3.
- Protects against sludging.
- Compatible with all gaskets and seals.

PERFORMANCE CHARACTERISTICS

SAE Grade 30

CCMC D2

MERCEDES-BENZ 227.0

API CD/SF

Military MIL-L-2104D

UNIVERSAL HD 30

TYPICAL INSPECTION

Properties	Unit	Value
SAE Grade		30
Viscosity @ 40°C	cSt	100
Viscosity @ 100°C	cSt	11.0
Density @15°C	g/mL	0.889
Sulphated Ash content	%	0.7