

OIL TECH

The Lubrication Specialists

TECHNICAL DATA SHEET

UNIVERSAL 15W/40

PRODUCT DESCRIPTION

UNIVERSAL 15W/40 A Super High Performance Petrol and Diesel engine lubricant designed to meet the requirements of European equipment, with and without turbocharger's in highway and construction vehicles.

APPLICATION

UNIVERSAL 15W/40 Super long-life, all-season SAE 15W/40 engine oil. Suited to long service in severe condition in both turbo-charged and normally aspirated heavy duty engines.

PERFORMANCE

- High detergency level ensures maximised engine cleanliness and minimal bore polishing or ring sticking.
- Excellent viscometrics produces a stay-in-grade and maintain quality even in the most severe conditions.
- Protects against sludging.
- Compatible with all gaskets and seals.
- Good corrosion protection even with high sulphur content fuels.

PERFORMANCE CHARACTERISTICS

ACEA E2-98

API CF-4/SJ

MAN 271

VOLVO-VDS

US Military Mil-L -2104F

CCMC-D4/PD2/G4

Mack EO-K/2 Pass

MERCEDES-BENZ 228.1

MTU Approval

UNIVERSAL 15W/40

TYPICAL INSPECTION

Properties	Unit	Value
SAE Grade		15W/40
Viscosity @ 40°C	cSt	123
Viscosity @ 100 °C	cSt	14.5
Density @ 15°C		0.89
Flash Point	C	228
Pour Point	C	-33
Sulphated Ash content	%	1.4